


## AC1200Mbps WiFi Gigabit Router



### KW65293Features:

- **High Speed:** Downstream rates up to 1000Mbps and upstream rates up to 1000Mbps
- **11AC 1200Mbps Wi-Fi:** Four external antennas to deliver the best wireless signal, connect everything in your home and office in one device
- **4 Gigabit Port Switch:** Extend the LAN to more devices and further distance allow up to 10 x higher speed
- **Multi-function USB2.0 Port:** Printers, files and media can be shared with computer or using the device's FTP server
- **High Power for wireless 2.4GHz:** Provide larger Wi-Fi range and more stable Wi-Fi connection
- **TR-069:** Manage settings and updates remotely from any end equipment
- **QOS:** Quality of Service control for traffic prioritization and bandwidth management
- **WPS Button:** Instant connection to wireless network safely
- **Simple set up with GUI:** GUI makes installation easier and faster

## ➤ Specifications

### BASIC

<b>Operation Modes</b>	Wireless Router, 5 Ports Switch, VoIP Gateway
<b>WAN Connection Types</b>	PPPoE, IPoE, Bridge

### WIRELESS

<b>Wireless Standards</b>	IEEE 802.11b/g/n/ac
<b>WiFi Frequency Range</b>	2.4GHz,5GHz
<b>WiFi Speed</b>	11n 2T2R up to 300Mbps 11ac 2T2R up to 900Mbps
<b>Antenna Gain</b>	5dbi
<b>Wireless Security</b>	64/128-bit WEP/WPA-PSK/WPA2-PSK/TKIP/AES
<b>Wireless Features</b>	Multi-SSID Access Control List Hide Access Point Clients Isolation Disable WMM Advertise Enable Wireless Multicast Forwarding (WMF) Wireless bridge MAC filter

### SOFTWARE

<b>Function Features</b>	Static Route, Dynamic RIPv1, RIPv2 Support DMZ Support NAT Application Level Gateway for popular applications DHCP Server/Relay/Client DNS Relay Agent/DDNS support PPP Auto Reconnect on WAN Access/PPP IGMP snooping v1/2 and IGMP Multicast IPv4 and IPv6 dual stack
<b>Security Support</b>	URL filter PAP/CHAP for PPP mode NAT for Firewall SPI Firewall 2 Level (User/Admin) Authentication to Router IP and MAC Filtering
<b>Management Support</b>	Web Based GUI FTP /HTTP/Telnet/TR069 /SNMP v1/2c Command Line Interface Diagnostic Test Firmware upgrade-able Remote Access Control
<b>PPP Features</b>	RFC2684 /2364 /2516 /1577/1483/2684
<b>VPN</b>	IPSec/PPTP/L2TP passthrough
<b>Port Forwarding</b>	Virtual server, Port Triggering, DMZ, ALG, UPnP
<b>Dynamic DNS</b>	DynDns, NO-IP
<b>DHCP</b>	Server, Client, DHCP Client List Address Reservation, DHCP relay
<b>QOS</b>	Priority Queuing Classification Rules 802.1p

### HARDWARE

<b>Physical Interface</b>	4 *GE LAN,1*Gigabit WAN,1*USB2.0
<b>Buttons</b>	Power /WiFi/WPS /Reset
<b>Power</b>	Input: 100-240V AC,50Hz; Output: 12V/1.5A
<b>LED Indicators</b>	Power, INET, WLAN 2.4G, WLAN 5G, WPS,LAN4/3/2/1, WAN, USB
<b>USB sharing</b>	Samba(Storage)/FTP Server/Media Server/Printer Server ( optional )
<b>Antenna</b>	4external antennas, MIMO5dBi (default)
<b>Processor</b>	RTL8685P+RTL8192ER+RTL8812AR
<b>Memory</b>	128MB RAM, 16MB FLASH

### OTHERS

<b>Operation System</b>	Windows 7,8,10, XP, VISTA/Macintosh/Linux
<b>Package Content</b>	Power Adapter x 1,InstallationManual x 1,RJ45 Cable 1.5M x 1,External Splitter x 1
<b>Environment</b>	Operating Temperature: 0°C~40°C(32~104°F) Storage Temperature: -30°C~60°C(-22~140°F) Operating Humidity: 10%~95% non-condensing Storage Humidity: 5%~90% non-condensing

## Package Content:



## ➤ Related products:



**KW5262B VDSL VoIP Gateway**

External 2T2R  
1 \*USB2.0  
1 \*DSL RJ-11 port  
2 \*FXS ports  
4 \*Fast LAN ports  
300Mbps Wi-Fi Speed



**KW6213 VDSL Modem Router**

External 4T4R and internal 1T1R  
2 \*USB3.0  
5\*GE LAN port  
1\*DSL port  
1600Mbps Wi-Fi Speed



**KW6263 VDSL VoIP Gateway**

External 4T4R and internal 1T1R  
2\*USB3.0  
2\* FXS port  
5 \*GE LAN port  
1\*DSL Port  
1600Mbps Wi-Fi Speed

