



KS105 5 Port Fast Ethernet Switch



Features

- **Plug and Play, Rapid Forwarding**
Play the device as long as you plug it, without any configuration. Rapid store-and-forward mechanism guarantee you a fluent and rapid online gaming, HD video and IP camera monitoring experience.
- **Mini and Fashionable Design**
The switch, with polished cambered checked white surface, is mini case and pocket design, smaller than your VISA card.
- **Wall & Desktop Mounting Design**
Support wall or desktop mounting. The wall-mounting guarantees a stable and firm network cabling when you deploy a network outdoor/indoor, like IP camera monitoring.
- **Green and Energy-saving**
Lower consumption: The max power consumption is 1.60W. It is low-carbon and energy saving.

Specification

Standards	IEEE 802.3, 802.3u, 802.3x
Basic Function	Wire-speed Performance MAC Address Auto-learning and Auto-aging IEEE 802.3x flow control for full-duplex mode and backpressure for half-duplex mode
MAC Address Table	1K
Switching Capacity	1.0Gbps
Forwarding Rate	10BASE-T: 14880pps/port 100BASE-TX: 148800pps/port
Transmission Method	Store-and-Forward
Access Control	CDMA/CD
MAC Address Learning	Automatic update
Interface	5*10/100Mbps Auto-Negotiation RJ45 ports (Auto MDI/MDIX)
Power Consumption	Maximum: 1.60W(220V)
Power supply	Input: AC:100-240V; 50/60Hz
	Output: 5.0V 0.6A (External Power Adapter)
Network Media	10Base-T: UTP category 3 or better 100Base-Tx: UTP category 5
LED Indicators	1 Power, 5 Link/Act
Product Dimensions	82mm*52mm*22.3mm (L*W*H)
Weight	120g
Safety and Emission	FCC, CE, RoHS
Environment	Operating Temperature: 0℃ ~40℃ (32°F~104°F) Storage Temperature: -40℃ ~70℃ (-40°F ~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing