

Wireless ADSL2+ Modem Router



KW58283 Features:

- **2.4G 300Mbps Wi-Fi:** Two internal antennas to deliver the best wireless signal, connect up to 16 devices in your home
- **High Speed:** Downstream rates up to 24Mbps and upstream rates up to 3.5Mbps
- **Operating distance:** up to 7KM
- **4-Port Switch:** Extent LAN to more devices and further distance
- **Multi-function USB2.0 Port:** Printers, files and media can be shared with computer or using the device's FTP server.
- **WPS Button:** Instant connection to wireless network safely
- **TR-069:** Manage settings and updates remotely from any end equipment
- **Compatibility:** Interoperable with all major DSLAM equipments
- **QOS :** Quality of Service control for traffic prioritization and bandwidth management
- **Simple set up with GUI:** GUI makes installation easier and faster

Specifications

BASICS

Operation Mode:	ADSL2+ Modem, 4 Port Switch
Speed:	11n speed up to 300Mbps Rate Adaptive: 32 Kbps steps
Frequency Range:	2,4Ghz-2,4835Hhz
Standard:	IEEE 802.11b/g/n Full-rate ANSI T1.413 issue 2 ITU-T G.992.1 /2/3/4/5 ITU-T G.994.1 (G.hs)
WAN Connection Type	DHCP ,Static IP, PPPoE, PPPoA, IPoA, Bridge, Multiple WAN
Wireless Features:	Multi-SSID Access Control List Hide Access Point Clients Isolation Disable WMM Advertise Enable Wireless Multicast Forwarding (WMF) Wireless Bridge MAC Filter

SOFTWARE

Protocol Supports	Static route, Dynamic RIPv1, RIPv2 support MTU Adjustment Network Address Translation (NAT) PVC Port Mapping (Ethernet ports) DMZ support NAT Application Level Gateway for popular applications DHCP Server/Relay/client DNS Relay Agent/DDNS support SNMP V1,V2 support UPnP (Universal Plug and Play) TR069 CWMP PPP Auto Reconnect on WAN Access/PPP on Demand IGMP v.1/v.2 snooping and IGMP Multicast
Security Support:	64/128-bit WEP/WPA-PSK/WPA2-PSK/TKIP/AES Parental control PAP/CHAP for PPP mode NAT for Firewall SPI Firewall Denial-of-service (DoS) protection ALG (Application-level gateway) for NAT/PAT support 2 Level (User/Admin) Authentication to Router IP and MAC Filtering
Management Support:	Web Based GUI FTP /HTTP/Telnet/TR069 /SNMP v1/2c Command Line Interface Diagnostic Test Firmware upgrade-able Supports Remote Access Control
ATM, PTM and PPP Features	RFC2684 /2364 /2516 /2225/1577 / 1483/2684 ATM Forum UNI 3.1/4.0, ATM Adaptation Layer Type 5-AAL5 VPI Range (0-255) and VCI range (32-65535) UBR, CBR, VBR-rt, VBR-nrt F4/F5 OAM Loopback AIS and RDI OAM cells Supports 16 PVCs
VPN:	IPSec /PPTP /L2TP pass through
Port Forwarding:	Virtual server, Port Triggering, DMZ, ALG, UPnP
Transmit Power:	<20dBm(EIRP)
Dynamic DNS:	DynDns, NO-IP
DHCP:	Server, Client, DHCP Client List Address Reservation, DHCP relay
QOS:	Priority Queuing Classification Rules
IPV6:	802.1p IPv4 and IPv6 dual stack

HARDWARE


Physical Interface:	4 *FE LAN, 1*DSL RJ11 port,1*USB2.0 port
Buttons:	Power /WPS /Reset
Power	Input: 100-240V AC,50Hz
LED Indicators:	Power,LAN1/2/3/4,WLAN,DSL,INTE,WPS, USB

Antenna:	Two internal antenna, MIMO 3dBi (default)
Processor	BCM6318+BCM43217T+BCM6301
Memory	8MB flash and 64MB RAM
USB sharing:	Samba(Storage)/FTP Server/Media Server/Printer Server

OTHERS

Operation System:	Windows 7,8,XP, VISTA/Macintosh/Linux
Package Content:	Power Plug x 1, Installation Manual x 1, RJ11 cable x 1 RJ45 cable x 1, External splitter x 1
Environment:	Operating Temperature: 0°C~40°C(32~104°F) Storage Temperature: -30°C~60°C(-22~140°F) Operating Humidity: 10%~95% non-condensing Storage Humidity: 5%~90% non-condensing
Dimension:	7.48*5.51*1.38 in (190*140*35mm)
Weight:	0.88 lbs (400 g)
Warranty	One year

Interface:



Package Content:



Related products:



KW58293 ADSL2+ Modem Router

Internal 2T2R
1* DSL port
4 *Fast LAN port
300Mbps Wi-Fi Speed



KW5813 ADSL2+ Modem Router

External 2T2R
1 *USB
4 *Fast LAN port
300Mbps Wi-Fi Speed



KW5863 ADSL2+ VoIP Gateway

External 2T2R
1 *USB
2* FXS port
1*DSL port
4 *Fast LAN port
300Mbps Wi-Fi Speed

